

End-of-Life Product



Chloride® CE-P - Rectifier

Overview

End of life announcement: July 2026

- Sales end date:
 - France 12/2026
 - Out of France 02/2026
- Last delivery dates for replacement parts: 01/07/2036 (according stock and obsolescence)

Replacement product:

- Chloride® DELTA DC Battery Chargers, tailored to specific applications and customer needs

End-of-Life Product Announcement

As part of our product portfolio management, we would like to inform you of our decision to discontinue sales of the CE-P rectifier. Some models in the lineup can be replaced by our DELTA 300 modules.



Chloride® CE-P

Chloride SAS offers a comprehensive range of industrial DC chargers and converters tailored to specific applications or individual customer needs. A wide variety of technologies and options are available across different product lines to meet most emergency power supply requirements in industrial or harsh environments.

CE-P

Code	Reference	Voltage		Output current (A)	Signage		
		Input (Vac)	Output (Vdc)		LED Status	Relay	58 311
6011054	CE-P 2.5 12	187 à 305 V 50/60Hz	12 V (10 - 15)	2.5 A	2	Non	Non
6011060	CE-P 08 12		12 V (10 - 15)	8 A	4	Oui	Oui
6007024	CE-P 05 12/24		12 V (10 - 15) 24 V (24 - 30)	5 A	4	Oui	Oui
6011062	CE-P 2.5 30/48		30 V (30 - 38) 48 V (48 - 60)	2.5 A	4	Oui	Oui

POWERIS equipped in CE-P

Reference	Voltage		Charger rating (A)	Battery Capacity (Ah)	Output Power (W)							Size (mm) H x L x P	Weight (Kg)
	Input (Vac)	Output (Vdc)			Sector	30'	1h	2h	4h	8h	12h		
POWERIS 330 24 05 07	230	24	5	07	103	-	96	54	32	18	-	300 x 333 x 203	11.5
POWERIS 445 24 05 14	230	24	5	14	86	-	-	108	78	36	26	450 x 497 x 253	20
POWERIS 445 24 05 24	230	24	5	24	62	-	-	-	128	67	44	450 x 497 x 253	29
POWERIS 445 24 05 40	230	24	5	40	5	-	-	-	-	126	78	450 x 497 x 253	39
POWERIS 445 24 05 48	230	24	5	48	223	-	-	-	-	-	88	450 x 497 x 253	50
POWERIS 445 48 2.5 07	230	48	2.5	07	86	-	192	108	64	36	26	450 x 497 x 253	20
POWERIS 445 48 2.5 14	230	48	2.5	14	53	-	-	-	128	72	52	450 x 497 x 253	30
POWERIS 645 48 2.5 24	230	48	2.5	24	5	-	-	-	256	134	88	600 x 497 x 253	60

End-of-Life Product



Chloride® CE-P - Rectifier

LUMERIS equipped in CE-P

Reference	DC Voltage	Available Power (W)			Size (mm)	Weight (Kg)
		Autonomy (mn)				
		60'	120'	180'		
LUMERIS 330 24 05 07 C V2	24 Vdc	100 W	60 W	40 W	300x333x203	13.5
LUMERIS 445 24 05 14 C V2		200 W	120 W	80 W	450x497x253	22
LUMERIS 445 24 05 24 C V2		360 W	200 W	160 W	450x497x253	29
LUMERIS 445 24 05 40 C V2		530 W	320 W	230 W	450x497x253	43
LUMERIS 445 24 05 48 C V2		720 W	400 W	320 W	450x497x253	50

ENERIS equipped in CE-P

Reference	Input Voltage (Vac)	Output Voltage (Vdc)	Output Specifications		Battery Autonomy (2h)	Size (mm)	Weight (Kg)
			Mains Power (W)	Peak Current (A)			
ENERIS 330 24 05 07 C V2	230	24	103	50	54	300 x 333 x 203	11.5
ENERIS 445 24 05 14 C V2	230	24	86	50	108	450 x 497 x 253	20
ENERIS 445 24 05 24 C V2	230	24	62	50	252	450 x 497 x 253	29
ENERIS 445 48 2,5 07 C V2	230	48	86	50	108	450 x 497 x 253	20

Replacement Products

For new projects, depending on the application and the customer's requirements, DELTA chargers may be offered as alternatives to the CE-P.

Code	Reference	Voltage		Current	Mecanical	Size (mm)	Weight (Kg)
		Input (Vac)	Output* (Vdc)	Output* (A)			
6014115	DELTA 300 12 10	187 to 264 V 47 to 63 Hz	12 V (0-15)	10	IP20	135 x 103 x 135	1
6014113	DELTA 300 24 10		24 V (0-30)	10			
6014114	DELTA 300 48 05		48 V (0-60)	5			

*via an external potentiometer

The POWERIS, LUMERIS, and ENERIS product lines mentioned above will eventually be equipped with DELTA. A selection chart will be provided.

For more information, our teams are here to help: hello@chloride.com

Chloride SAS, 30, Avenue Montgolfier, BP 90 - 69684 Chassieu - France T: +33 (0)4 78 40 13 56 Hello@Chloride.com

Pour trouver le contact dans votre région, veuillez consulter le site www.chloride.com

© 2026 Chloride SAS. Tous droits réservés. Chloride, le logo Chloride sont des marques ou des marques déposées de Chloride. Tous les autres noms et logos cités sont des noms commerciaux, des marques ou des marques déposées de leurs propriétaires respectifs. Bien que toutes les précautions aient été prises pour assurer l'exactitude et l'exhaustivité de ce document, Chloride, n'assume aucune responsabilité, et décline toute responsabilité, pour les dommages résultant de l'utilisation de ces informations ou pour toute erreur ou omission. Les spécifications peuvent être modifiées sans préavis.